



PERMIT FOR TILE CROSSING SECONDARY ROAD IN THE PUBLIC RIGHT-OF-WAY IN CERRO GORDO COUNTY, IOWA

I, the undersigned, hereby requests permission to tile across a Secondary Road in Cerro Gordo County.

Describe the location of the proposed crossing:

Size of connecting tile: Outlet: _____ Inlet _____ Direction of flow: _____

Crossing tile size: _____ Proposed material: _____ Perforated: ___ yes ___ no

Proposed Contractor _____

Anticipated date of construction: _____

Estimated cost of Installation: _____ feet of tile \$ _____ per foot equals \$ _____

Applicant name: _____

Mailing Address: _____

City: _____ State _____ Zip _____

Email: _____

Contact telephone Number: _____

Owner ___ yes ___ no If no, what is owner's name _____

Adjacent landowner: _____

Mailing Address: _____

City: _____ State _____ Zip _____

Email: _____

Contact telephone Number: _____

Specifications

Crossings that occur along county lines will be administratively handled by the County with maintenance jurisdiction. Crossings that occur on the common line between County and City must have concurrence from both entities before work is completed.

County Engineer reserves the right to deny the crossing if it is determined that adequate surface drainage and crossroad structures are present.

Crossings under paved roads shall be bored. Crossing under granular surfaced roads may be open trenched. Applicant, or their agent, shall compact backfill, remove excess material, reshape, and reseed all areas disturbed to the original condition of the right of way.

For open trenched crossings, the full width of the roadbed shall be backfilled in lifts of 8" or less, with suitable material and proper compaction. The top one (1) foot of backfill material shall consist of crushed limestone, provided by the applicant. County shall be given the opportunity to inspect the crossing before being backfilled. Open trenched crossings shall not be performed between November 15th and April 1st unless specifically authorized by the County Engineer.

Material must be of rigid construction from 10' into private property, through the right of way, to 10' into private property. Engineer may require corrugated metal pipe be used in lieu of dual walled plastic for factors like depth. County Engineer may require non-perforated pipe be used within the right to right of way in areas populated by willows or willow-like plants or trees or the potential for willow growth or regrowth.

Private tile shall not be permitted to be outlet into the road right of way ditch, unless specifically authorized by the County Engineer. Ditch grades will not be lowered for the expressed purpose of accommodating tile outlets. If upon review, the ditch segment has silted in higher than the original ditch grade, the County Engineer will authorize the necessary cleaning. Scope of such ditch cleaning is based on County needs and scheduling.

Cerro Gordo County shall be notified forty-eight (48) hours in advance of the start of drainage construction operations in the public right of way.

